

# GP/GPT系列直立式耐酸碱泵

GP/ GPT SERIES VERTICAL ACID AND ALKALI RESISTANT PUMP



可空转使用，绝不因空转而损坏。

泵浦所有接液部分，均采用耐腐蚀之FRPP、CPVC、PVDF材质，视输送的化学药剂而定。

GP/GPT系列采用C型卡簧和入口滤网装置，入口主体体积较小，更适合槽内设计使用。

在马达输出轴处及泵浦底部分别装置耐酸碱之密封件，双层保护可防止化学气体损坏马达轴承，而游离之化学气体将经由支撑板上的气孔顺利排出。

特殊设计之叶轮，即使叶轮偶尔逆转也不会损坏泵浦。

泵浦出口有PP和PVC两种接头，供客户方便使用。

Can be used idling not damaged due to idling.

Then fluid pumped all part of using corrosion-resistant FRPP, CPVC, PVDF material, depending on the chemical transmission of the liquid GP/GPT series using C-mount and the entrance of filter devices, the main entrance of smaller, more suitable for the use of bed design

At motor output shaft and pumped separately at the bottom of the device seals acid, double-layer protection to prevent damage to motor bearings chemical gases, and off-axis of the chemical gas will be distributed through on-board support from the stomatal smoothly.

Special design of the impeller, even the occasional reversal of the impeller will not damage the pump.

Outlet has two types of PP and PVC joints for ease of use customers.

## 型号识别 Model identification

GP - 40 VK 1 6 V F

① ② ③ ④ ⑤ ⑥ ⑦

①系列代码 Series Symbol	GP SERIES GPT SERIES
②出口口径 Size	25:1" 40:1-1/2" 50:2"
③比重 Specific Weight	VK:1.1 VP:1.4
④马力 Motor Power	1/2:1/2HP 1:1HP 2:2HP 3:3HP 5:5HP

⑤频率 Frequency	5:50HZ 6:60HZ
⑥O环 O-Ring	V-VITON E-EPT N-NBR
⑦泵浦材质 Pump Material	F-FRPP P-PVDF C-CPVC

## 规格表 Specifications

型号 Model	比重 Specific Gravity	进出口径 In-outlet (mm)	马力 Power			50HZ			60HZ			重量 Weight (kg)
			相数 Phase	HP	极数 Poles	曲线 NO	扬程 Head(m)	流量Flow (L/min)	曲线 NO	扬程 Head(m)	流量Flow (L/min)	
GP-25VK-1/2	1.1	40×25	1/3	1/2	2	e	13	160	E	13	165	18
GP-40VK-1	1.1	50×40	1/3	1	2	f	12	280	F	15	350	19
GP-40VK-2	1.1	50×40	3	2	2	g	14	320	G	19	400	24
GP-25VP-1	1.4	40×25	1/3	1	2	i	11	200	I	12	185	18
GP-40VP-1	1.4	50×40	1/3	1	2	j	10	230	J	11	230	18
GP-40VP-2	1.4	50×40	3	2	2	k	11	250	K	15	280	24

## 外形尺寸图

Dimensional drawing, part drawing

